

# Tyre Spotter




CP - 1  
Shoulder Plate - Top -  
120 mm



CP - 2  
Shoulder Plate - Top -  
100 mm



CP - 3  
Crown \ side Plate  
Top - 120 mm



CP - 4  
Crown \ side Plate  
Top - 100 mm



CP - 5  
Crown \ Shoulder side \  
wall Plate - Bottom  
- 120 mm



CP - 6  
Crown \ Shoulder side \  
wall Plate - Bottom  
- 100 mm

## Future :

- Tyre Spotter is the most economical car tyre repair equipment, suit of variety of models of tyres to be completed single-sided or double-sided parts of the vulcanizing operation inbuilt thermostat-controlled, ensure that the tyre vulcanizing temperature required, according to the different type of tyre position, to do vulcanization job. With Six different angles module and a special thermal silicon bags to make sure the tyre recover as the original shape after repair.

## Specification :

- Voltage : 220V
- Watts : 1000 W ( 500 X 2 )
- Temperature:140-150°C
- Timer Scope : 0-120 Minutes

## Note :

- The power cord must be securely grounded,
- Must be cut off the power when you replace the Fuse.
- To be carefully when need to remove the hot heater to avoid burns.
- The Equipment must be away from the acid and other corrosive materials.
- If the balancing head sticky dirt after you use, it need polished and clean, otherwise it will affect the flatness, smoothness of the tyre.

